

TESAB



TS3600

3 DECK SCREENER

The TS3600 3 Deck Screener builds from the huge success of the TS2600 and takes Screening Capacity and Performance to a different level.

The addition of a Third Deck in the Screenbox, Cross Conveyor and Fourth Product Conveyor, you get even more return for your investment with the same exceptional reliability and production quality as the TS2600.

Adjustable screenbox angles makes the TS3600 incredibly adaptable. It exceeds in a wide range of applications including Quarrying, Crusher Circuits, Sand and Gravel, Coal, Topsoil and Woodchip.

Made from the highest quality components you can rely on this machine to keep on producing for you, even when you need it to perform in the toughest of applications.

FEATURES & BENEFITS

- 20' x 5' (6.1m x 1.52m) super high performance Screenbox
- High quality components makes this one of the most dependable machines on the market
- Hydraulic folding conveyors throughout so set up times and costs are significantly lower
- An extremely adaptable machine that exceeds in a huge range of applications

SCREENER



14ft (4267mm) grid opening allows the use of larger loading shovels.

The most advanced 20x5 (6.10m x 1.52m) portable vibratory screening plant in production.

42" (1050mm) feed conveyor enables high capacity screening.

User friendly wedge system ensures faster screen changes.

Hydraulic Screenbox linkage system, allows great accessibility for screen change and enables optimum screen coverage at varying screenbox angles.

PERFORMANCE SPECIFICATION

* Depending on application

Max Feed Size*	Engine Size	Top Deck	Bottom Deck	Middle Deck
up to 650 TPH	CAT 125Hp (93Kw)	6.10m x 1.52m (20' x 5')	5.49m x 1.52m (18' x 5')	6.10m x 1.52m (20' x 5')

DIMENSION SPECIFICATION*

* Depending on material density and set-up

TRANSPORT DIMENSIONS			WORKING DIMENSIONS		
Height	Width	Length	Width	Length	Weight (Est.)
3450mm (11' 4")	3220mm (10' 7")	18,450mm (60' 6")	18,280mm (60')	19,610mm (64' 4")	36,500kgs (80,468lbs)